

Remote control device

# SRCS-RIO-42

## “Universal” remote control device for managing digital inputs and relay outputs

This device allows remote control of 4 digital inputs and 2 relay outputs.

The control unit is configurable and manageable via sending SMS commands. You can also control the outputs from a weekly timer with four daily slots.

### TECHNICAL FEATURES

- Power supply: 12 – 24 “VDC” / “VAC” 50/60Hz
- Modem GSM Dual Band
- 4 digital inputs (contact)
- 2 relay outputs 6(2) A 250Vca (contact NO)
- Battery included for sending an SMS in case of power failure



### FUNCTIONAL FEATURES

- Configuration via SMS
- You can configure up to 4 phone numbers
- You can attach a description to each input for sending an SMS in clear
- 4 inputs for which an SMS is sent at every change of status (the inputs are configurable and can be used as standard inputs or so that they can generate an SMS at every status transition)
- 2 relay outputs controlled directly by sending an SMS (outputs can be controlled as set/reset or of impulsive type)
- Outputs can be controlled by a weekly timer programmed through SMS sending

### DIMENSIONAL FEATURES

- Hooks on DIN EN 607 guide
- Colour: Grey RAL 7035
- Material: PPO self-extinguishing
- Dimensions: 4 DIN modules

### PRODUCT CODE

SRCS-RIO-42	Remote control device with 4 inputs and 2 outputs
SRCS-RIO-42-B	Remote control device with 4 inputs and 2 outputs, internal battery for sending power failure SMS
SRCS-RIO-42-2TB	Remote control device with 4 inputs and 2 outputs, internal battery for sending power failure SMS and outputs that can be controlled by a weekly timer
SRCS-RI-4	Remote control device with 4 inputs
SRCS-RI-4-B	Remote control device with 4 inputs and internal battery for sending power failure SMS

### RELATED PRODUCTS

SG-ANT-AS1	Wall-fixed antenna, with 3 metres cable
SG-PRO-05	5 metres antenna extension
SG-ANT-AB1	High gain dipole Antenna with 5 m cable, pole-fixed